



hot finish coating	
hot end coating	
cold end coating	

客户批准信息/CUSTOMER APPROVAL	
审批意见 DESIGNATION	
签字/SIGNATURE	
日期/DATE	

耐水性能/HYDROLYTIC RESISTANCE	*** 级/grade
应力等级/TRESS	≤ 4 级/grade
垂直负荷/VERTICAL LOAD	≥ *** N
抗冲击力/IMPACT STRENGTH	≥ *** J
内压强度/INTERNAL PRESSURE	≥ *** MPa
抗热震性能/THERMAL SHOCK	≥ 42 °C
瓶口椭圆度/OVALITY FINISH	≤ *** mm
瓶身椭圆度/OVALITY BODY	≤ *** mm
垂直轴偏差/VERTICALITY	≤ 2.8 mm
口平面不平度/BENT FINISH	≤ 0.5 mm
口对底平行度/HORIZONTALITY	≤ 1.0 mm
瓶肩壁厚/SHOULDER THICKNESS	≥ 1.5 mm
瓶身壁厚/BODY THICKNESS	≥ 1.5 mm
瓶跟壁厚/HEEL CONTACT THICKNESS	≥ 1.5 mm
瓶底壁厚/BASE THICKNESS	≥ 2.5 mm

技术规范/SPECIFICATION

满口容量 BRIMFUL CAP	2750±25	CC	成型工艺 PROCESS	P&B	设计/DESIGN	L.T.	27-06-2020	D/M/Y	瓶口标准 FINISH	WGF-165S 100 regular	图纸版次/REV.
灌装容量 FILLING CAP	---	CC	玻璃料色 COLOR		审核/REVISION				产品编号 REGISTER		2
灌装线 FILLING LEVEL	---	mm	翻到角度 TILT ANGLE	---	批准/APPROVE				产品名称 JOB NAME	2750ml jar	
重量 WEIGHT	875±35	g			比例/SCALE	1:1	图纸尺寸使用单位 ALL DIMENSIONS ARE IN mm		Brother Glass Mould MFG Co.,Ltd		
客户名称/CUSTOMER			兄弟玻璃模具有限公司享有图纸所有权!未经允许,不得复制、使用、转抄								